



MCB-64A0003M0A

Article number: 218572

1/2,9" HD Camera 2560x1440, Day&Night, AF Zoom
WDR, 3,2-9 mm, Infrared, IP67

Mainfeatures

1/2,9" 6,64 Megapixel SONY STARVIS CMOS-Sensor

Integrated connection box with circuit board

Optical 3x auto focus zoom, 3,2~9mm

Multisignal: HD-TVI, AHD selectable, Composite SUB

DOL-WDR by triple scan images at 30/25fps &

Point of Interest & Smart Motion Zoom

Resolution max. 2560x1440@25/30fps

Simple and tidy wiring

Separate outputs for digital and multi-signal

Digital signal: EX-SDI, HD-SDI selectable

ROI (Region of Interest) WDR mode

IR illumination switchable via OSD menu

Specifications

Camera:	
Sensor size	1/2.9"
Resolution pixels	2560x1440, 1920x1080, 1280x720
Imager	CMOS, Sony STARVIS, Sensor IMX326
System	True Day&Night
Sensitivity	0,1 Lux, at F1.6, 40IRE
Low speed shutter	yes, 2x ~ 32x
Manual electronic shutter (MES)	1/25 ~ 1/30.000sec
Automatic electronic shutter (ESC)	1/25 ~ 1/30.000sec.
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR, WDR 113dB, Real Time WDR 25/30fps
Flickerless function	yes

MCB-64A0003M0A

Continued Specifications

Backlight compensation	BLC, HLC
Day/Night switching	auto, day, night
IR cut filter	switchable
White balance	AUTO, AUTOext, manual, Preset
Signal-to-noise ratio	50dB
Video:	
Video standard	PAL/NTSC
Signal format	HD-TVI, AHD, EX-SDI (270 Mbps), HD-SDI (1.485 Gbps)
Frame rate	25/30fps @ 1440p, 25/30fps @ 1080p, 50/60fps @ 720p
Lens:	
Lens type	auto focus zoom
Zoom factor	3x
Focal length	3,2 - 9 mm
Digital zoom	yes
MOD (Minimum object distance)	0,5 m
Aperture range (F)	F1.6
Iris control	DC
Vertical angle of view	42 - 3 °
Horizontal angle of view	78 - 6 °
Features:	
Motion detector	yes
OSD function control	OSD camera setup
Menu languages	English, German, Japanese, Chinese, Korean
Privacy zones masking	Areas-ON/OFF switchable
Mirror function	V flip, H-flip, H/V flip
Digital Noise Reduction (DNR)	yes
Interfaces / Inputs / Outputs:	
Video outputs	HD-TVI, AHD, composite (CVBS) SUB, EX-SDI, HD-SDI
External connections	voltage input, 1x SDI Signal (BNC), 1x HD Analog Signal (BNC)
Alarm inputs	no
Alarm outputs	no
Serial interfaces protocols	Pelco C (UTC / HD-TVI)
General:	
Series	eneo Candid Small
Dimensions (HxWxD)	130,5x82,15x265,8mm
Illumination	infrared, 4x High Power LEDs 850nm
Illumination range	approx. 40m
Colour (housing)	Pantone Cool Gray 1C
Housing	outdoor
Housing material	aluminium
Weight	1.25kg
Integrated wall mount	yes
Power consumption	9.5W
Blower	no

MCB-64A0003M0A

Continued Specifications

Mounting	wall mount, ceiling mount
Window heater	yes
Protection rating	IP67
Hidden cable management	yes
Sunshield	yes
Supply voltage	12VDC, 24VAC
Temperature range (operation)	-20°C ~ +50°C
Text display	supplied
Vandalism resistant	no
Scope of delivery:	
Parts supplied	manual, Video sub-out cable, bag of screws

Special features

Integrated connection box

Pointing Zoom -- enables the flexible zooming at any area

Preset Zoom (4 adjustable positions)

MCB-64A0003M0A

Available Accessories

Image	Prod. No / Label	Description
	202641 / PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, Candid L, W3, WB1, AK-5, AK-4
	70527 / NE-132/AC24V	Power Supply Unit 230VAC/24VAC (1.0A)
	211257 / HDA-3000E	HD Extender, HD-SDI, EX-SDI, 12V
	212984 / TVA-1201TRA	HD-TVI Transmitter+Receiver, UTP, BNC, 250m, Indoor, Active, 12V
	212985 / TVA-1201TRP	HD-TVI Transmitter+Receiver, 150m, BNC, UTP, Indoor, Passive
	212987 / TVA-1101EA	HD-TVI Signal Amplifier, 12VDC, Indoor
	214236 / TAM-4MM1001M0A	HD-TVI Converter to HDMI, VGA, FBAS, Indoor
	217344 / MAM-5ME1001MTA	Multisignal Converter, HD-TVI , AHD, 960H to IP, H.264, 1920x1080, 12VDC
	218653 / PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com