



MAM-5MM1001M0A

Article number: 220299

Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor

Mainfeatures

Converter HD-TVI, AHD, CVI, CVBS to HDMI, VGA, CVBS

Display simultaneously HDMI, VGA and CVBS signal

HD-TVI, AHD, CVI input: 720p@25/30/50/60Hz, 1080p@25/30Hz

HDMI, VGA output: 480p, 576p, 720p, 1080i, 1080p

CVBS output: PAL/NTSC

Power LED, Link LED

Built in OSD to display input/output setting

PIP display under dual camera input mode

Specifications

Signal format	HD-TVI, AHD, CVI, Composite (FBAS)
Resolution max.	1920x1080
Interfaces / Inputs / Outputs:	
Video inputs	BNC-female
Video inputs (amount)	1
Video inputs (type)	HD-TVI, AHD, CVI, composite (CVBS)
Video outputs	HDMI, VGA
General:	
Dimensions (HxWxD)	30x88x130mm
Colour	anthracite / black
Housing	aluminium
Weight	275g
Power consumption	5W
Supply voltage	12VDC
Temperature range (operation)	0°C ~ +55°C

MAM-5MM1001M0A

Continued Specifications

Scope of delivery:

Parts supplied	manual, bag of screws, PSU
----------------	----------------------------

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com