

AXIS P1275 Network Camera

Complete, discreet HDTV 1080p varifocal dome

AXIS P1275 Network Camera is a compact and cost-effective varifocal dome camera with HDTV 1080p for discreet indoor surveillance in stores, offices, and banks. The camera comes with an adjustable field of view, which makes it ideal for both wide area coverage and detailed view. Equipped with WDR – Forensic Capture, enables the camera to handle scenes with strong variations in light. Sensor unit rotates and tilts to the desired viewing direction. AXIS P1275 comes with a mounting bracket and an 8 meter (26 feet) detachable cable.

- > **HDTV 1080p resolution**
- > **WDR – Forensic Capture**
- > **99° – 53° horizontal field of view**
- > **Axis Zipstream**
- > **Power over Ethernet**



AXIS P1275 Network Camera

Camera		Data streaming	Event data
Image sensor	1/2.9" (effective) progressive scan RGB CMOS	General	
Lens	Fixed iris, varifocal 2.8 – 6.0 mm, F2.0 Horizontal field of view: 99°–53° Vertical field of view: 53°–30°	Casing	AXIS P12 Mk II Main Unit: Steel and plastic Sensor unit: Plastic, aluminum
Minimum illumination	Color: 0.22 lux	Sustainability	PVC free
Shutter time	1/32500 to 2 s	Memory	512 MB RAM, 256 MB Flash
Camera angle adjustment	Pan: 360° Tilt: 0 to 90° Rotation: 360°	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2 Max 4.0 W, typical 2.5 W
Video		Connectors	Female RJ45 for 10BASE-T/100BASE-TX PoE RJ12 for sensor unit
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Resolution	1080p	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Frame rate	25/30 fps (50/60 Hz)	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Approvals	EMC EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 62368-1 Environment EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure value, exposure control, exposure zones, local contrast, rotation, corridor format, WDR - forensic capture, text and image overlay, privacy mask, mirroring of images	Dimensions	AXIS P12 Mk II Main Unit: 16.5 x 46 x 109 mm (5/8 x 1 13/16 x 4 5/16 in) AXIS FA4115 Dome Sensor Unit: min 50 mm (2 in), max 71 mm (2 13/16 in), ø 88 mm (3 8/16 in) Sensor unit cable: 8 m (26 ft)
Network		Weight	AXIS P12 Mk II Main Unit: 72 g (2.5 oz) AXIS FA4115 Dome Sensor Unit: 112 g (3.95 oz) Sensor unit cable: 128 g (4.5 oz)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, Digest authentication, User access log, Centralized certificate management, signed firmware	Included accessories	Installation Guide, Windows [®] decoder 1-user license 8-m (26 ft) black cable, mounting bracket
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP [™] , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	Optional accessories	AXIS T8120 15 W Midspan 1-port AXIS T8129 PoE Extender Network cable coupler indoor slim AXIS Surveillance Cards AXIS F7315 Cable White 15 m For more accessories, see axis.com
System integration		Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform (ACAP); specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Warranty	AXIS 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Cross Line Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (eyay@cryptsoft.com).	
Event triggers	Analytics Edge storage events	Environmental responsibility: axis.com/environmental-responsibility	
Event actions	File upload: email, FTP, HTTP, HTTPS, network share Notification: email, HTTP, HTTPS and TCP Pre- and post-alarm video buffering Send SNMP trap, WDR mode		
Built-in installation aids	Pixel counter		