

AXIS P1377-LE Network Camera

Fully-equipped 5 MP surveillance for the great outdoors

With a robust design, AXIS P1377-LE offers excellent 5 MP video and can withstand extreme temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F). For extra protection an optional weathershield is available. It delivers great details in challenging or low light and includes Axis OptimizedIR for surveillance in pitch darkness. Designed as a deterrent, it includes electronic image stabilization, shock detection, tampering alarm and video streaming indicator. Axis Zipstream supporting H.264/H.265 provides exceptional savings on bandwidth and storage. Plus, with CS mount and support for motorized i-CS, you can easily change lens to meet your requirements.

- > 30 fps in 5 MP or up to 180 fps in HDTV 720p
- > OptimizedIR and Forensic WDR
- > Signed firmware and secure boot
- > Electronic image stabilization
- > Zipstream supporting H.264 and H.265



AXIS P1377-LE Network Camera

Camera	
Image sensor	1/2.7" progressive scan RGB CMOS
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8 mm, F1.2 Horizontal field of view: 90°–38° Vertical field of view: 67°–28°
Day and night	Automatically removable infrared-cut filter
Minimum illumination	HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder: Color: 0.13 lux, at 50 IRE F1.2 B/W: 0.03 lux, at 50 IRE F1.2 0 lux with IR illumination on
Shutter time	WDR: 1/33500 s to 1/5 s No WDR: 1/50000 s to 1/5 s
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG Controllable frame rate and bandwidth
Resolution	2592x1944 (5 MP) to 160x90 2688x1512 (4 MP) to 160x90 1280x720 (HDTV 720p) to 160x90
Frame rate	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 4 MP: 25/30 fps (50/60 Hz) Capture mode HDTV 720p: 180 fps
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator
Multi-view streaming	Up to 8 individually cropped out view areas
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)
Audio	
Audio streaming	Two-way, full duplex
Audio compression	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate
Audio input/output	External microphone input, line input, digital input with ring power, line output
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP
System integration	
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at axis.com AXIS Guardian with One-Click Connection ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org
Onscreen controls	Electronic image stabilization Day/night shift Defogging

	Wide dynamic range
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Live Privacy Shield, AXIS Perimeter Defender, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Event triggers	Analytics, shock detection, open casing, edge storage events, supervised external input, audio level, time scheduled
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation Send SNMP trap
Data streaming	Event data
Built-in installation aids	Focus assistant, pixel counter, remote back focus, autorotation, remote focus and zoom and with optional i-CS lens.
General	
Casing	IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure with aluminium base and intrusion alarm switch Weathershield with black anti-glare coating Color: White NCS S 1002-B
Sustainability	PVC free
Memory	1 GB RAM, 512 MB Flash
Power	12–28 V DC, max 19.1 W, typical 10.5 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 2 Class 4, max 20.4 W, typical 11.1 W With disabled IR: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 12.95 W, typical 6.7 W Power redundancy
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T I/O: 6-pin 2.5 mm terminal block, for 2 supervised alarm inputs and 2 outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range 50 m (164 ft) or more, depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Absolute maximum temperature: 74 °C (165 °F) according to NEMA TS2 2016, 2.2.7 Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC 62471 Environment IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X, NEMA TS2 2016 (Subsection 2.2.7-2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, IEC/EN 60529 IP67 Network NIST SP500-267

Dimensions	404 x 159 x 168 mm (15.9 x 6.3 x 6.6 in)
Weight	2.4 kg (5.3 lb)
Included accessories	Installation Guide, Windows® decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool Torx® T20 screw driver, Torx® T30 screw bit AXIS P13 Weathershield Kit A pre-mounted AXIS Fixed Box IR Illuminator Kit A
Optional lenses	Lens Computar i-CS 2.8-8.5 mm Tamron 5 MP Lens P-Iris 8-50 mm F1.6 Lens i-CS 9-50 mm F1.5 8 MP
Optional accessories	Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS P13 Weathershield Extension A AXIS T8355 Digital Microphone AXIS T99A11 Positioning Unit 24 V AC/DC

For more accessories, see axis.com

Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>	

Environmental responsibility:

axis.com/environmental-responsibility