



VM-FHD32M

Article number: 217914

32" (82cm) LCD Monitor FHD, 1920x1080, LED, HDMI, VGA Composite, Metal cabinet

Professional 32" (82 cm) LCD monitor

Industrial design built to run 24x7x365 continuously

Maximum resolution 1920x1080 pixels

LED Back Light

Fast response time 5ms

Perfect presentation through digital 3D filtering and noise reduction

Different video inputs HDMI,VGA, Composite

Built-in speakers

Supply voltage: 240-100VAC, 50/60Hz

Metal cabinet including stand

Specifications

Display:	
Synchronization	internal
Resolution	1920x1080 (16:9)
Aspect ratio	16:9
Resolution pixels	1920x1080
Contrast ratio typical	1300:1
Response time typical	5 ms
Brightness typical	300 cd/m ²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	32"
Screen Size (cm)	80,1 cm
Pixel format	0,51075mm x 0,51075mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, 2x composite (CVBS)
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3,5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	442,8x732,8x85,1mm
Total height with stand	500mm
Mount	VESA standard 200x200mm
Housing material	metal
Housing color	black
Weight	12kg
Loudspeaker	2
Power consumption	40W
Supply voltage	100 ~ 240VAC, 50/60Hz
Temperature range (operation)	-30°C ~ +85°C
Scope of delivery:	
Parts supplied	manual, power cord, IR remote controller, VGA cable, feet

Related Products



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

