



## VM-FHD10M

Article number: 225695

10" (25cm) LCD Monitor FHD, 1920x1080, LED, HDMI, VGA, Composite

Professional 10" (25 cm) LCD monitor

Industrial design built to run 24x7x365 continuously

Maximum resolution 1920x1080 pixels

LED Back Light

Fast response time 5ms

Perfect presentation through digital 3D filtering and noise reduction

Different video inputs HDMI, VGA, Composite

HD analog multi signal input (TVI, AHD, CVI)

Supply voltage: 12VDC

Metal cabinet including stand

## Specifications

Display:	
Synchronization	internal
Resolution	1920x1080 (16:9)
Aspect ratio	16:9
Resolution pixels	1920x1080
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	350 cd/m <sup>2</sup>
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	10,1
Screen Size (cm)	25,6 cm
Pixel format	0,630mm x 0,630mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, 2x HDMI, composite (CVBS), HD-TVI, AHD, CVI
Input signals	HD-TVI up to 5MP, AHD up to 5MP, CVI up to 4MP
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3,5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	185x260x18mm
Total height with stand	215mm
Mount	VESA standard 75x75mm
Housing material	metal
Housing color	black
Weight	4.5Kg
Loudspeaker	2
Power consumption	10W
Supply voltage	12VDC
Temperature range (operation)	-30°C ~ +85°C
Scope of delivery:	
Parts supplied	manual, power cord, PSU 100-240VAC, IR remote controller, VGA cable, feet

## Related Products



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

