



IEB-72M2812MAA 9005

Article number: 228518

1/2,8" Network camera, 1920x1080, Day/Night, WDR, 2,7-12mm, IR, IP66, RAL9005

1/2,8" Sony STARVIS CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 1920x1080, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 2,7~12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	PoE IEEE 802.3af Class 0, 12VDC, IP66
Wide Dynamic Range, T-WDR (120dB)	Supports ONVIF Profile S und Profile T
Quad Streaming: Smart Codec ROI Hi-Stream	Colour RAL 9005, black

Specifications

Camera:		Features:	
Camera type	Bullet	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Sensor size	1/2,8"	Privacy zones masking	Areas-ON/OFF switchable
Resolution standard	HD 1080p	Remote configuration	web browser
Imager	CMOS, Sony STARVIS, Sensor IMX290	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
System	True Day&Night	User interface	Type B (white / blue)
Sensitivity	0,03 Lux, at F1.6, 40IRE	Mirror function	H-flip, mirror
Low speed shutter	yes, automatic	Digital Noise Reduction (DNR)	yes
Manual electronic shutter (MES)	1~1/10000Sek.	Network:	
Automatic electronic shutter (ESC)	1~1/10.000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Wide Dynamic Range (WDR)	WDR 120dB	Interfaces / Inputs / Outputs:	
Flickerless function	yes	Video outputs	no
Backlight compensation	Smart BLC	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Day/Night switching	day, night, auto	Ethernet interface	10Base-T, 100Base-TX
IR cut filter	switchable	Alarm inputs	1
White balance	automatic, manual	Alarm outputs	1
		Serial interfaces	Ethernet
Video:		General:	
Resolution	1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	Series	eneo SN-Series
Resolution max.	1920x1080	Dimensions (HxWxD)	86x90x279mm
Image display	VerticalView 90°/270°, 4:3, 16:9, 5:4	Illumination	infrared, 34x LED 850nm
Stream types	Quad Streaming	Illumination range	approx. 30m
Image transmission rate max.	30 fps	Colour (housing)	RAL9005
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG	Housing	outdoor
		Housing material	aluminium
Lens:		Weight	860g
Lens type	Varifocal (motorized)	Integrated wall mount	yes
Zoom factor	4x	Power consumption	9W
Focal length	2,7 - 12 mm	Blower	no
Digital zoom	yes	Mounting	wall mount, ceiling mount
MOD (Minimum object distance)	0,5 m	ONVIF	ONVIF Profile S, ONVIF Profile T
Iris control	P-iris, DC	Power over Ethernet	IEEE 802.3af
Vertical angle of view	56 - 18 °	Window heater	no
Horizontal angle of view	100 - 33 °	Protection rating	IP66
DORI:		SDK	upon request
Detection (25 px/m)	40 - 130 m	Hidden cable management	yes
Observation (62 px/m)	16 - 55 m	Sunshield	yes
Recognition (125 px/m)	8 - 26 m	Supply voltage	12VDC, PoE
Identification (250 px/m)	4 - 13 m	Temperature range (operation)	-20°C ~ +50°C
Features:		Text display	supplied
Multicast compliant	yes	Vandalism resistant	no
Motion detector	yes	Scope of delivery:	
Analysis functions	motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog, motion detection	Parts supplied	manual, bag of screws
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out, Alarm Forwarding (Preset Call of eneo PTZ Dome)	Notes:	
Audio	2 Way Audio	Remarks	Note that electronic adjustment aid such as Zoom / Focus or Pan / Tilt functions are not designed for continuous operation. Permanent use may affect the life of the camera
Audio support	yes		
Password protection	yes		
e-PTZ support	yes		
Internal storage	microSDHC card, microSDXC card		

Related Products



AK-8B RAL 9005|SKU: 228517


Product recommendations



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



eneo Site Manager|SKU: 218218

