



IPD-52M2712M5A

Article number: 227058

1/2,8" Network Dome, Fix, 1920x1080, Day&Night, DOL-WDR, 2,7-12mm, Infrared, IP66

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 1920x1080 (Full HD)	Triple Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7-12mm	Responsive Web Design, Zero Configuration
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE or 12VDC
Motion Detection, Privacy Zones, Defog	For outdoor use IP66, vandal proofed IK10
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:		Features:	
Camera type	Dome	Privacy zones masking	Areas-ON/OFF switchable
Sensor size	1/2.8"	Remote configuration	web browser
Resolution standard	HD 1080p	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Imager	CMOS, Sony STARVIS, Sensor IMX307	User interface	Type A (orange / grey)
System	True Day&Night	Mirror function	mirror, flip
Sensitivity	0,06 Lux, at F1.3, 40IRE	Digital Noise Reduction (DNR)	yes
Low speed shutter	yes, 1x-10x	Network:	
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Interfaces / Inputs / Outputs:	
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR	Video outputs	no
Flickerless function	yes	External connections	12VDC input (DC plug), RJ-45, connection cable approx.15cm
Backlight compensation	BLC, HLC	Ethernet interface	10Base-T, 100Base-TX
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)	Alarm inputs	no
IR cut filter	switchable	Alarm outputs	no
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes	Serial interfaces	Ethernet
Signal-to-noise ratio	50dB	General:	
Video:		Series	eneo LN-Series
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Dimensions (HxWxD)	108x144,4mm
Resolution max.	1920x1080	Illumination	infrared, 30x LED 850nm
Image display	VerticalView 90°/270°, 4:3, 16:9	Illumination range	approx. 30m
Stream types	Multi Streaming	Colour (housing)	Pantone Cool Gray 1C
Image transmission rate max.	30 fps	Colour (bubble)	clear
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG	Housing	outdoor, indoor
Lens:		Housing material	aluminium
Lens type	Varifocal (motorized)	Weight	1.1kg
Zoom factor	4x	Heater	no
Focal length	2,7 - 12 mm	Power consumption	8W
Digital zoom	yes	Blower	no
MOD (Minimum object distance)	0,5 m	Mounting	wall mount, ceiling mount
Iris control	DC	ONVIF	ONVIF Profile S, ONVIF Profile T
Vertical angle of view	54 - 18 °	Power over Ethernet	IEEE 802.3af
Horizontal angle of view	103 - 33 °	Protection rating	IP67
Features:		SDK	upon request
Multicast compliant	yes	Supply voltage	12VDC, PoE
Motion detector	yes	Temperature range (operation)	-20°C ~ +50°C
Analysis functions	motion detection, Defog	Text display	supplied
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out	Vandalism resistant	yes
Audio support	no	Certificates	IK10
Password protection	yes	Scope of delivery:	
e-PTZ support	yes	Parts supplied	manual, bag of screws
Internal storage	no		
Menu languages	English, German, French, Korean		


Product recommendations



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472



eneo Site Manager|SKU: 218218

