



# IPB-62M2712M5A

Article number: 227060

1/2,8" Network Camera, 1920x1080, Day&Night, DOL-WDR, 2,7-12mm, Infrared, IP66

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
Resolution max. 1920x1080 (Full HD)	Triple Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~12mm	Responsive Web Design, Zero Configuration
DOL-WDR (120dB)by triple scan images at 30/25fps	Power supply PoE or 12VDC
Motion Detection, Privacy Zones, Defog	For outdoor use IP66
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

## Specifications

Camera:	
Camera type	Bullet
Sensor size	1/2,8"
Resolution standard	HD 1080p
Imager	CMOS, Sony STARVIS, Sensor IMX307
System	True Day&Night
Sensitivity	0,06 Lux, at F1.3, 40IRE
Low speed shutter	yes, 1x~10x
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR
Flickerless function	yes
Backlight compensation	BLC, HLC
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)
IR cut filter	switchable
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Signal-to-noise ratio	50dB

Video:	
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)
Resolution max.	1920x1080
Image display	VerticalView 90°/270°, 4:3, 16:9
Stream types	Multi Streaming
Image transmission rate max.	30 fps
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

Lens:	
Lens type	Varifocal (motorized)
Zoom factor	4x
Focal length	2,7 - 12 mm
Digital zoom	yes
MOD (Minimum object distance)	0,5 m
Iris control	DC
Vertical angle of view	54 - 18 °
Horizontal angle of view	103 - 33 °

Features:	
Multicast compliant	yes
Motion detector	yes
Analysis functions	motion detection, Defog
Alarm processing	E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping
Audio support	no
Password protection	yes
e-PTZ support	yes
Internal storage	no
Menu languages	English, German, French, Korean

Features:	
Privacy zones masking	Areas-ON/OFF switchable
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
User interface	Type A (orange / grey)
Mirror function	mirror, flip
Digital Noise Reduction (DNR)	yes

Network:	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour

Interfaces / Inputs / Outputs:	
Video outputs	no
External connections	RJ-45, 12VDC input (DC plug)
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Ethernet

General:	
Series	eneo LN-Series
Dimensions (HxWxD)	78,5x78,5x214mm
Illumination	infrared, 4x High Power LEDs 850nm
Illumination range	approx. 40m
Colour (housing)	Pantone Cool Gray 1C
Housing	outdoor
Housing material	aluminium, plastic
Weight	520g
Integrated wall mount	yes
Power consumption	8,5W
Blower	yes
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Window heater	no
Protection rating	IP66
SDK	upon request
Hidden cable management	yes
Sunshield	yes
Supply voltage	12VDC, PoE
Temperature range (operation)	-20°C ~ +50°C
Text display	supplied
Vandalism resistant	no

Scope of delivery:	
Parts supplied	manual, bag of screws


## Product recommendations



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218

