



ICB-68M3611M5A

Article number: 220592

1/2,5" Network Camera 3840x2160, Day&Night, DOL-WDR 3,6-11 mm, Infrared, IP67

1/2.5" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest)
4K UHD Resolution 3840x2160, @25/30fps	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 3,6~11mm	Slot for Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE IEEE 802.3af
VCA video analysis, ONVIF event mapping	Integrated connection box with sabotage contact and circuit board
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

Camera:	
Camera type	Bullet
Sensor size	1/2.5"
Resolution standard	4K Ultra HD
Imager	CMOS, Sony STARVIS, Sensor IMX274
System	True Day&Night
Sensitivity	0,2 Lux, at F1.5, 40IRE
Low speed shutter	yes, 1x~10x
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Wide Dynamic Range (WDR)	DOL-WDR 120dB, D-WDR
Flickerless function	yes
Backlight compensation	BLC, HLC
Day/Night switching	auto, day, night, night-color mode, extern (Sensor)
IR cut filter	switchable
White balance	ATW-Indoor, ATW-Outdoor, manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammies
Signal-to-noise ratio	50dB

Video:	
Resolution	3840x2160 (16:9), 2592x1520 (16:9), 1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)
Resolution max.	3840x2160
Image display	VerticalView 90°/270°, 4:3, 16:9
Stream types	Multi Streaming
Image transmission rate max.	30 fps
Compression standard	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG

Lens:	
Lens type	Varifocal (motorized)
Zoom factor	3x
Focal length	3,6 - 11 mm
Digital zoom	yes
MOD (Minimum object distance)	0,5 m
Iris control	DC
Vertical angle of view	46 - 21 °
Horizontal angle of view	84 - 40 °

Features:	
Multicast compliant	yes
Motion detector	yes
Analysis functions	motion detection, Field detection, Defog, Line detection
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out
Audio	2 Way Audio
Audio support	yes
Password protection	yes
e-PTZ support	yes
Internal storage	microSDHC card, microSDXC card

Features:	
Menu languages	English, German, French, Korean
Privacy zones masking	Areas-ON/OFF switchable
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
User interface	Type A (orange / grey)
Mirror function	mirror, flip
Digital Noise Reduction (DNR)	yes

Network:	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour

Interfaces / Inputs / Outputs:	
Video outputs	no
External connections	micro SD card slot, Connection board (LSA, RJ45, audio, I / O alarm & Sabotage contacts)
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	1
Alarm outputs	1
Serial interfaces	Ethernet

General:	
Series	eneo Candid Small, eneo LN-Series
Dimensions (HxWxD)	130,5x82,1x265,1mm
Illumination	infrared, 4x High Power LEDs 850nm
Illumination range	approx. 40m
Colour (housing)	Pantone Cool Gray 1C
Housing	outdoor
Housing material	aluminium
Weight	1.25kg
Integrated wall mount	yes
Power consumption	9,2W
Blower	yes
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Window heater	no
Protection rating	IP67
SDK	upon request
Hidden cable management	yes
Sunshield	yes
Supply voltage	PoE
Temperature range (operation)	-50°C ~ +50°C
Text display	supplied
Vandalism resistant	no

Scope of delivery:	
Parts supplied	manual, bag of screws

Related Products



PM-42A | SKU: 202641

More product information

Integrated connection box with sabotage alarm contact, Simple wiring, the integrated connection board offers the possibility of network cabling via LSA connection bar or RJ45 socket. Terminal block for connection of alarm contacts and audio.


Product recommendations



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472



eneo Site Manager | SKU: 218218

